

BS BATTERY TYPE	CAPACITY Ah (10Hr)	CAPACITY Ah (20Hr)	CCA (EN) A (-18°C)	DIMENSIONS mm (±2mm)			ASSEMBLY LAYOUT	TERMINAL
				L	W	H		
BTR4A-BS	2.3	2.4	45	113	48	85		I
BT4B-BS	2.3	2.4	40	113	38	85		J
BT4L-BS	3	3.2	60	113	70	85		A
BTX4L-BS+ NEW	4	4.2	50	113	70	85		A
BT4AL-BS	4	4.2	60	120	70	92		A
BT5L-BS	4	4.2	80	113	70	105		A
BTX5L-BS	4	4.2	80	113	70	105		A
BT5AL-BS	5	5.3	65	120	60	130		B
BTX7L-BS	6	6.3	100	113	70	130		A
BTX7A-BS	6	6.3	105	150	87	93		A
BT7B-BS	6.5	6.8	110	150	65	93		A
BTZ7S-BS	6	6.3	130	113	70	105		A
BTX9-BS	8	8.4	135	150	87	105		A
BT9A-BS	9	9.5	115	135	75	139		A
BT9B-BS	8	8.4	120	150	70	105		A
BTZ10S-BS	8.6	9	190	150	88	93		A
BTZ12S-BS	11	11.6	215	150	88	110		A
BTX12L-BS	10	10.5	180	150	87	130		A
BTX12-BS	10	10.5	180	150	87	130		A
BT12A-BS	10	10.5	175	150	88	105		A
BT12B-BS	10	10.5	210	150	70	130		A
BTX14L-BS	12	12.6	200	150	87	145		A
BTX14-BS	12	12.6	200	150	87	145		A
BT14B-BS	12	12.6	210	150	69	145		A
BTX14AHL-BS	12	12.6	210	135	90	164		A
BTX14AH-BS	12	12.6	210	133	90	164		A
BTZ14S-BS	11.2	11.8	230	150	88	110		A
BTX15L-BS	13	13.7	230	175	87	130		A
BTX15-BS	13	13.7	230	175	87	130		A
BTX16L-BS	14	14.7	230	150	87	161		A
BTX16-BS	14	14.7	230	150	87	161		A
BTX16-BS-1	14	14.7	230	150	87	161		E
BT16CL-BS	19	20	260	175	100	175		A
BTX18L-BS	18	18.9	250	205	87	162		A
BTX18-BS	18	18.9	250	205	87	162		A
BTX20A-BS	18	18.9	270	150	87	161		A
BTX20L-BS	18	18.9	270	175	87	155		A
BTX20-BS	18	18.9	270	175	87	155		A
BTX20HL-BS	18	18.9	310	175	87	155		A
BTX20HL-BS-PW	18	18.9	310	175	87	175		A
BTX20H-BS	18	18.9	310	175	87	155		A
BTX20CH-BS	18	18.9	270	150	87	161		A
SLA12-19-BS	19	20	275	172	77	168		G
BTX24HL-BS	21	22.1	350	205	87	162		A
BIX30L-BS	30	31.6	400	166	126	174		A

TERMINAL TYPE	A	B	C	D	E	F	G	H	I	J
3D DRAWING										